Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100

Size	Hon		Pereme Heigh		Custom 1	Custom2		Definition Bettom		Mode (Length		
0.25	0.0	0.0	0.0	0.0	Ю	0	0.0	0.0	0.0	3.0	0	
2. 0.0	0.0	0.0	0.0	0.0	О	0	0.0	0.0	0.0	0.0	10	Ar Su
3 0.0	0.0	0.0	00	0.0	0	D	0.0	0.0	0.0		0	
4. 0.0	0.0	10.0	0.0	0.0	0	Jo	0.0	0.0	0.0	0.0	10	
5 00	0.0	0.0	0.0	0.0	0	0	0.0	ver this way	0.0	0.0	0	
6 0.0	0.0	0.0	0.0	0.0	lo	0	0.0	0.0	0.0	and the second	10	
? [0.0	0.0	0.0	0.0	0.0	0	0	0.0	0.0	0.0	0.0	0	
8 0.0	0.0	0.0	0.0	0.0	o	0	0.0	0.0	0.0	0.0	0	
9: 0.0	0.0	0.0	0.0	0.0	0	lo .	0.0	0.0	0.0	4	lō .	
10- 0.0	0.0	0.0	0.0	0.0	Jo	0	0.0	0.0	0.0	7.2	lo .	
	GF9 0.0 0.0 0.0 0.0 0.0 0.0	Facure (Abs: 10.0 (0.0 (0.0 (0.0 (0.0 (0.0 (0.0 (0.0	0.0 10.0 0.0 10.0 0.0 1 0.0 1 0.0 1 0.0 1	G58 0.0 0.0 0.0 0.0 0.0 0.0	655 0.0 0.0 0.0 0.0 0.0 0.0	/ Ble	code Displa Splids vs. w grante (mat cak Skip Cha cak Skip Cha sch Frie N an Central (U) (N)	inde Feed h (Speed Per to France h and positio	Selfs) Dengt Totals	•		
	10.0	(00)	0.0	0.0]	0.0 0.0 of Photos	FR Conv	3key	3 [

FIG 1.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 2.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 3.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 4.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 5.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 6.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 7.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100




FIG 8.

Inventor: Gary John Corey Application No. 10/079,309 Inventor's Phone No.: (909) 674-8100

9/9

```
N10 T01 M6
N20 G90 S200 M3
N30 GO A270. BO
N40 X0 Y-21. Z0 M8
N50 Z20.5
N60 G1 Y-10.933 Z17.9365 A270. B-30. F10.
N70 Y-3.2465 Z10.75 A270. B-60.
N80 Y0 Z.5 A270. B-90.
N90 Y-3.2465 Z10.75 A90. B-60.
N100 Y-10.933 Z17.9365 A90. B-30.
N110 Y-21. Z20.5 A90. B0
N120 G1 Z0
N130 G0 A0 B0
N140 X0 Y-21. Z0 S200 F10.
N150 G1 Z20.5
N160 G1 Y-10.9332 Z17.9367 A0 B-29.9993 F10.
N170'Y-3.2463 Z10.7498 AO B-60.0007
N180 Y0 Z.5 A0 B-90.
N190 Y-3.2465 Z10.75 A180. B-60.
N200 Y-10.933 Z17.9365 A180. B-30.
N210 Y-21. Z20.5 A180. B0
N220 Z0
N230 GO AO BO
N240 M30
```

FIG 9.